

## AMENDMENTS TO THE SPECIFICATION

Rewrite the paragraph beginning at the top of page 6 as follows:

FIG. 4 is a plan view of the frame 12. Referring to FIGS. 1, 2 and 4, the frame 12  
5 includes a coupling portion 40 a support portion 41, and a base portion 42. The  
grill attachment portion 40 includes four upstanding slotted grill attachment  
brackets 44, each of which includes a slotted portion having a number of grill  
attachment slots 46, extending between flat sides of the slotted portion from a  
narrow edge of the slotted portion, and arranged to accept the distal ends 48 of  
10 the food grills 14. Each of the food grills 14 can be moved vertically from one  
pair of slots 46 in adjacent grill attachment brackets 44 to another to vary the  
distance between the fire 18 and the grill 14. While each of the slots 46 has an  
open end 50 that is preferably enlarged to permit easy entry of the distal end 48,  
the slots 46 are preferably configured to hold the grills 14 to extend nearly  
15 horizontally. In the example of the figures, each of the grill attachment brackets  
44 additionally includes a twisted portion 52, extending between the slotted  
portion of the grill attachment bracket 44 and a lower portion of the grill  
attachment bracket 44 providing for attachment to an upper crossbar 54, which  
holds the attachment brackets 44 so that each of the grills 14 is held in a pair of  
20 adjacent brackets 44, with a flat side of the lower portion of the grill attachment  
bracket 44 being attached to the upper crossbar 54.

Rewrite the paragraph beginning at line 15 of page 6 as follows:

The support portion 41 of the frame 12, which extends downward from the  
25 coupling portion 40, includes upper legs of a pair of L-shaped stand brackets 56  
extending vertically between the upper crossbar 54 and the base portion 42,  
being attached to the upper crossbar 54, with the upper crossbar 54 holding the  
grill attachment brackets 44 horizontally spaced apart from one another and from  
the upper legs of the stand brackets 56. The base portion 42 includes lower legs  
30 of the L-shaped stand brackets 56. The base portion 42 additionally includes a

front crossbar 56 and a rear crossbar 58 extending between the L-shaped stand brackets 56. The base portion 40 includes a pair of small L-shaped brackets 62 extending rearward from the L-shaped stand brackets 62 to provide additional stability on the fireplace floor 24.

5